

# hepair<sup>2000</sup>

## Dust aspiration and filtration system

Hepair 2000 offers a triple stage of filtering [G4 + M5 + HEPA H13], which will retain all the particles, choosing them by their thickness with the different modules.

Its compact and robust design with wheels and lateral handles, facilitates a better portability and maneuverability within the facilities.



VOLTAGE  
110V / 220V

HEPA  
FILTERING

INDICATOR  
FILTER  
SATURATION

LOW  
NOISE LEVEL

UNE  
100.012

## APPLICATIONS

CIRCULAR  
DUCT

FIBRE  
DUCT

SQUARE  
DUCT

SECTION  
200 to  
800 mm

Triple filtration:  
pre-filter G4 + M5 bag  
filter + H13 absolute filter



## OPTIONAL ACCESSORIES



ASPIRATION HOSE  
Ø160 mm - 3 m of length


COD. AC3101308



EXTENSIBLE STICK  
For suction hose. Extendable  
from 160 to 290 cm. 2 units.

COD. AC3101303

## CONSUMABLES



THICK PREFILTER  
G4

10 units. COD. AC3101305



BAG FILTER M5

COD. AC3101306



HEPA13 FILTER

COD. AC3101309

## TECHNICAL FEATURES

Supply voltage	230 V - 50 Hz [4 A] 110 V - 60 Hz [8 A]
Maximum vacuum volume	2000 m³/h 1177,2 cfm
Maximum depression	2500 Pa - 0,36 psi
Triple filtration 3 F	Prefilter G4 Bag filter M5 HEPA H13 Absolute filter
Separation degree	>99%
Engine power	880 W
Noise level	72 dB
Dimensions [L x W x H]	611 x 590 x 943 mm 24 x 23 x 37 inches
Weight	80 kg   176,37 lb



VACUUM SYSTEMS IN DUCTS